

<b>general data</b>				
operating voltage	V	230		
measurements	cm			
Stand-alone		85 x 60 x 60		
Built-in		82 - 87 x 60 x 57		
Built-in		81,6 - 88,0 x 60 x 54,6		
capacity ( standard place settings)	N	12		
power draft complete	W	2200		
<b>Water capacity in tub (about)</b>	I			
Appliance with rotary-slide				
final rinse		~ 3,4		
all other rinse		~ 3,7		
Appliance without rotary-slide				
without Impulse-rinse		~ 4,2		
with Impulse-rinse		~ 3,8		
water pressure (max/min)	N/cm <sup>2</sup>	100/10		
<b>technical features</b>		50 Hz	60 Hz	
<b>drain pump</b>				
max. height	cm	100	100	
pump rate	l/min	15	15	
power input	W	26	26	
winding resistance	Ω	180	120	
<b>dispenser combination</b>				
capacity	cm <sup>3</sup>	140		
dosing area	cm <sup>3</sup>	2 - 7		
resistor	Ω	1360		
<b>regenerating valve</b>				
resistor	Ω	3000		
<b>water inlet valve</b>				
delivery rate	l/min	4		
winding resistance	Ω	3750 - 4000		
<b>heater resistance</b>				
1. element power input	Ω	2100		
protector	°C	98 ± 5 K		
thermal fuse	°C	260		
resistor	Ω	25		
<b>circulation pump</b>				
motor operating capacitor	mF	50 Hz 4	50 Hz 4	60 Hz 4
power input / output	W	100/50	100/30	100/50
rotary speed	min-1	2800	2800	2800
current input	A	0,6	0,6	0,6
main winding resistance	Ω	51	59	35
auxiliary winding resistance	Ω	160	146	106
tacho winding resistance	Ω	213	213	/
<b>Rotary slide</b>				
rotary speed	min-1	/	0,5	/
resistor	Ω	/	9300	/
<b>pressure switch</b>				
switch on/off pressure	mmWs	fN = 65/45	fS = 114/90	
<b>transformer</b>				
voltage primary/secondary	V	230/5V A		
power input primary / second.	mA	35/454		
resistor	Ω	460/1,4		
<b>fan in the door</b>				
resistor	Ω	740		
<b>fan on the tub</b>				
resistor	Ω	896		
<b>servo door lock</b>				
resistor	Ω	7500		
rotary speed	min -1	2		

<b>Temperature sensor NTC-resistor</b>	
temperature/resistor	20 °C / 6032 Ω
	25 °C / 4829 Ω
	30 °C / 3891 Ω
	40 °C / 2573 Ω
(only for fully electronic dishwasher)	50 °C / 1741 Ω
	55 °C / 1444 Ω
	60 °C / 1204 Ω
	65 °C / 1009 Ω
	70 °C / 849 Ω